



HSE Explosion proof solenoid valve · Exd IIC T5 IP65


방폭용 솔레노이드 밸브(5-WAY TYPE) / Certification No. 20-GA2BO-0325X

HYO SHIN ELECTRIC CO., LTD.




▶형식(MODEL) 방폭코일 5-WAY TYPE

MODEL NO.	VOLTAGE	Hz	WATTAGE	REMARK
H5A-220660	AC 220V	60Hz	6±10%	STANDARD
H5A-240650	AC 240V	50Hz	6±10%	OPTION
H5A-100660	AC 100V	50/60Hz	6±10%	OPTION
H5A-110660	AC 110V	60Hz	6±10%	OPTION
H5D-024060	DC 24V	-	6±10%	STANDARD
H5D-012060	DC 12V	-	6±10%	OPTION
H5D-100600	DC 100V	-	6±10%	OPTION



외형도(DIMENSIONS)

CABLE CONNECTION LINE 주문시 선택



사양서(SPECIFICATIONS)

구분 (CLASSIFICATION)	표준 사양 (STANDARD)	구분 (CLASSIFICATION)	표준 사양 (STANDARD)	옵션 사양 (OPTION)
사용유체 (FLUID)	AIR (공기)	사용전압 (RATED VOLTAGE)	AC-220V 60Hz DC-24V	AC-240V 50Hz AC-100V 50/60Hz AC-110V 60Hz DC-100V DC-12V
유체온도범위 (FLUID TEMP.)	0 ~ 60°C	몸체재질 (BODY MAT'L)		AL
사용압력범위 (PRESSURE RANGE.)	1.5 ~ 10bar	씨트재질 (SEAT MAT'L)		NBR
온도등급 (TEMPERATURE RATING.)	T5 (85°C 초과 100°C 이하)	몸체접속방식 (END CONN.)		PT(Rc) 1/4"
코일절연 종별 (INSULATION GRADE)	CLASS H	밸브중량 (WEIGHT)		1.0Kg

*기타사양은 HSE에 문의 요망, 도면치수 및 제품사양은 품질향상을 위해 변경될수 있음
CONSULT WITH HSE ABOUT OTHER OPTION SPECIFICATIONS, PRODUCT SPECIFICATION IS TO SUBJECT TO THE QUALITY ENHANCEMENT.